



## ISO/IEC 19752 Yield Test Report

### MS810 Print Cartridge

Printer MS810

Declaration of Yield: **Average Cartridge Yield 6,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 6,748  
**Std Dev** 163  
**90% Lower Confidence** 6,647

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

|  |              |                                  |
|--|--------------|----------------------------------|
|  | <b>start</b> | <b>stop</b>                      |
| <b>Date Tested</b>                     | 7-May-2012   | 8-May-2012                       |
| Number of cartridges in testing        |              | 9                                |
| Qty. of cartridges used in calculation |              | 9                                |
| Shake Procedure                        |              |                                  |
|  | 1st shake    | No Shake                         |
|  | 2nd shake    | No Shake                         |
| Print mode                             |              | Continuous                       |
| Number of printers tested              |              | 3                                |
| Media used                             |              | Orange Paper - 80gsm - A4        |
| Paper feed orientation                 |              | Short Edge Feed (SEF)            |
| Driver version                         |              | Gold 9                           |
| Operating system                       |              | Windows XP SP3                   |
| Application software                   |              | Acrobat version 9.1              |
| Test page version                      |              | ISO_IEC_19752_2004_Test_Page.pdf |

| Cartridge testing data: | Cartridge       | Printer       | Temperature |           |           | Humidity |     |     | Cartridge Yield | Cart used in Calculation |
|-------------------------|-----------------|---------------|-------------|-----------|-----------|----------|-----|-----|-----------------|--------------------------|
|                         |                 |               | Avg (F/C)   | Max (F/C) | Min (F/C) | Avg      | Max | Min |                 |                          |
|                         | (S)CAS120545DFB | 4063127900002 | 73          | 78        | 69        | 41       | 48  | 37  | 6,863           | Y                        |
|                         | (S)CAS120545DF8 | 4063127900002 | 73          | 78        | 69        | 41       | 48  | 37  | 6,887           | Y                        |
|                         | (S)CAS120545DF9 | 4063127900002 | 73          | 78        | 69        | 41       | 48  | 37  | 6,719           | Y                        |
|                         | (S)CAS120555B98 | 4063127900005 | 73          | 78        | 69        | 41       | 48  | 37  | 6,762           | Y                        |
|                         | (S)CAS120555B91 | 4063127900005 | 73          | 78        | 69        | 41       | 48  | 37  | 6,872           | Y                        |
|                         | (S)CAS120555B95 | 4063127900005 | 73          | 78        | 69        | 41       | 48  | 37  | 6,706           | Y                        |
|                         | (S)CAS120545E1E | 4063127900010 | 73          | 78        | 69        | 41       | 48  | 37  | 6,401           | Y                        |
|                         | (S)CAS120545E17 | 4063127900010 | 73          | 78        | 69        | 41       | 48  | 37  | 6,617           | Y                        |
|                         | (S)CAS120545DF7 | 4063127900010 | 73          | 78        | 69        | 41       | 48  | 37  | 6,905           | Y                        |

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.