



ISO/IEC 19752 Yield Test Report

MS812 Print Cartridge

Printer MS812

Declaration of Yield:
Average Cartridge Yield 25,000 Standard Pages
Declared yield in accordance with ISO/IEC 19752

Average 29,078
Std Dev 1,151
90% Lower Confidence 28,364

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	19-Jul-2012	8-Aug-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1219231FB	40631279000BB	72	75	69	48	55	42	28,611	Y	
(S)CAS1219231D5	40631279000BB	72	75	69	48	55	42	30,132	Y	
(S)CAS1219231F7	40631279000BB	72	75	69	48	55	42	28,552	Y	
(S)CAS1219231F8	4063127900043	72	75	69	48	55	42	27,885	Y	
(S)CAS1219231D0	4063127900043	72	75	69	48	55	42	27,437	Y	
(S)CAS1219231EB	4063127900043	72	75	69	48	55	42	28,639	Y	
(S)CAS1219231F0	406312790004K	72	75	69	48	55	42	31,046	Y	
(S)CAS1219231F9	406312790004K	72	75	69	48	55	42	29,844	Y	
(S)CAS1219231E6	406312790004K	72	75	69	48	55	42	29,553	Y	

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.