

LEXMARK ISO/IEC 19752 Yield Test Report

MS812 Extra High Yield Print Cartridge Printer MS812

Declaration of Yield: **Average Cartridge Yield 45,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 47,538
Std Dev 1,783
90% Lower Confidence 46,433

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 31-May-2012	<u>stop</u> 8-Jun-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAN121080373	40631279000BB	72 / 22.2	75 / 23.8	68 / 20	42	48	38	49,775	Y
(S)CAN121080393	40631279000BB	72 / 22.2	75 / 23.8	68 / 20	42	48	38	47,990	Y
(S)CAN1210704DE	40631279000BB	72 / 22.2	75 / 23.8	68 / 20	42	48	38	50,050	Y
(S)CAN1210704DC	4063127900043	72 / 22.2	75 / 23.8	68 / 20	42	48	38	47,125	Y
(S)CAN121080395	4063127900043	72 / 22.2	75 / 23.8	68 / 20	42	48	38	45,015	Y
(S)CAN12108038E	4063127900043	72 / 22.2	75 / 23.8	68 / 20	42	48	38	47,990	Y
(S)CAN1210704DD	406312790004K	72 / 22.2	75 / 23.8	68 / 20	42	48	38	46,480	Y
(S)CAN121080371	406312790004K	72 / 22.2	75 / 23.8	68 / 20	42	48	38	45,180	Y
(S)CAN12108038F	406312790004K	72 / 22.2	75 / 23.8	68 / 20	42	48	38	48,240	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.