



# ISO/IEC 19752 Yield Test Report

## MS817 Print Cartridge

Printer: MS817

Declaration of Yield: **Average Cartridge Yield 11,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 12,703  
**Std Dev** 642  
**90% Lower Confidence** 12,305

**For questions concerning testing contact**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 20-Apr-2017	<u>stop</u> 24-Apr-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX710 Series XL
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAB17090155A	40636C660330B	73	74	72	58	60	57	12,040	Y
SCAB1709014E4	40636C660330B	73	74	72	58	60	57	12,450	Y
SCAB170901507	40636C660330B	73	74	72	58	60	57	12,741	Y
SCAB17090159E	40636C660330V	73	74	72	58	60	57	11,727	Y
SCAB170901515	40636C660330V	73	74	72	58	60	57	12,452	Y
SCAB170901592	40636C660330V	73	74	72	58	60	57	13,115	Y
SCAB170901533	40635C6608CTP	73	74	72	58	60	57	12,633	Y
SCAB170901582	40635C6608CTP	73	74	72	58	60	57	13,431	Y
SCAB170901510	40635C6608CTP	73	74	72	58	60	57	13,736	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.