



# ISO/IEC 19752 Yield Test Report

## MS818 Print Cartridge

Printer: MS818

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>11,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 13,249  
**Std Dev** 514  
**90% Lower Confidence** 12,930

**For questions concerning testing contact**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 20-Apr-2017	<u>stop</u> 24-Apr-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX710 Series XL
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAB170901598	40636C6600YFX	73	74	72	58	60	57	12,757	Y
SCAB170901587	40636C6600YFX	73	74	72	58	60	57	12,976	Y
SCAB170901573	40636C6600YFX	73	74	72	58	60	57	13,886	Y
SCAB1709014E0	40636C6600YFW	73	74	72	58	60	57	13,760	Y
SCAB1709014E3	40636C6600YFW	73	74	72	58	60	57	13,795	Y
SCAB170901520	40636C6600YFW	73	74	72	58	60	57	13,456	Y
SCAB17090153F	40636C6604PXZ	73	74	72	58	60	57	13,320	Y
SCAB170901536	40636C6604PXZ	73	74	72	58	60	57	12,817	Y
SCAB17090156C	40636C6604PXZ	73	74	72	58	60	57	12,475	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.