



# ISO/IEC 19752 Yield Test Report

## MS823/MS824 Starter Print Cartridge

Printer: MS823/MS824

Declaration of Yield	<b>Average Cartridge Yield</b>	<b>11,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 12,337  
**Std Dev** 416  
**90% Lower Confidence** 12,079

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 11-Jan-2018	<u>stop</u> 12-Jan-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17320112A	4064PTBGLA165	74	76	73	49	50	48	12,209	Y
CAS173201127	4064PTBGLA165	74	76	73	50	53	48	12,637	Y
CAS173201121	4064PTBGLA165	74	76	73	50	53	48	12,960	Y
CAS17320111B	4064PTBGLA166	74	76	73	49	50	48	11,615	Y
CAS173201126	4064PTBGLA166	74	76	73	50	53	48	11,828	Y
CAS1732010E6	4064PTBGLA166	74	76	73	50	53	48	12,484	Y
CAS17320112F	4064PTBGLA173	74	76	73	49	50	48	12,271	Y
CAS1732010D8	4064PTBGLA173	74	76	73	50	53	48	12,406	Y
CAS1732010FA	4064PTBGLA173	74	76	73	50	53	48	12,619	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.