

MS825/MS826 Extra High Yield Toner Cartridge

Printer: MS825/MS826

Declaration of Yield:

Average Cartridge Yield	35,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 39,342
Std Dev 3369
90% Lower 37,254
Confidence

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	6-Feb-2018	10-Feb-2018

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
1st shake	No shake
2nd shake	Continuous
Print mode	3
Number of printers tested	Hammermill Tidal MP - 20 lbs. - Letter
Media used	Short Edge Feed (SEF)
Paper feed orientation	47_G3
Driver version	Window 7 Professional
Operating system	Adobe Acrobat version 9
Application software	ISO_IEC_19752_2004_Test_Page.pdf
Test page version	ON
Power (off/on) everyday	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210196	4064PTBGLA162	73	75	72	51	53	50	40,332	Y
CAS173210192	4064PTBGLA162	73	75	72	51	53	49	40,705	Y
CAS173210150	4064PTBGLA162	73	75	72	50	53	49	39,477	Y
CAS173210198	4064PTBGLA163	73	75	72	51	53	50	42,295	Y
CAS17321019B	4064PTBGLA163	73	75	72	51	53	49	42,496	Y
CAS173210152	4064PTBGLA163	73	75	72	50	53	49	40,953	Y
CAS173210197	4064PTBGLA164	73	75	72	51	53	50	38,692	Y
CAS173210153	4064PTBGLA164	73	75	72	51	53	49	37,775	Y
CAS17321013E	4064PTBGLA164	73	75	72	50	53	49	31,355	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.