



ISO/IEC 19752 Yield Test Report

MS911 Ship With Equipment Print Cartridge

Printer MS911

| | | | |
|--|--------------------------------|---------------|-----------------------|
| Declaration of Yield: | Average Cartridge Yield | 21,000 | Standard Pages |
| Declared yield in accordance with ISO/IEC 19752 | | | |

Average 22,250
Std Dev 1504
90% Lower Confidence 21,318

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

| | <u>start</u> | <u>stop</u> |
|--|--------------|---|
| Date Tested | 28-Feb-2014 | 4-Mar-2014 |
| Number of cartridges in testing | | 9 |
| Qty. of cartridges used in calculation | | 9 |
| Shake Procedure | | |
| | 1st shake | No Shake |
| | 2nd shake | No Shake |
| Print mode | | Continuous |
| Number of printers tested | | 3 |
| Media used | | Hammmermill Tidal MP - 20 lbs. - Letter |
| Paper feed orientation | | Long Edge Feed (LEF) |
| Driver version | | B11 |
| Operating system | | Windows XP SP3 |
| Application software | | Acrobat version 9 |
| Test page version | | ISO_IEC_19752_2004_Test_Page.pdf |

| Cartridge testing data: | | Temperature | | | Humidity | | | Cartridge Yield | Cart used in Calculation |
|-------------------------|---------------|-------------|-----------|-----------|----------|-----|-----|-----------------|--------------------------|
| Cartridge | Printer | Avg (F/C) | Max (F/C) | Min (F/C) | Avg | Max | Min | | |
| CRT_MUSTANG_09 | PTBMFPHV51008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 21,137 | Y |
| CRT_MUSTANG_10 | PTBMFPHV51008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 20,738 | Y |
| CRT_MUSTANG_11 | PTBMFPHV51008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 21,143 | Y |
| CRT_SORENTO_016 | PTBSFPHV51014 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 24,099 | Y |
| CRT_SORENTO_017 | PTBSFPHV51014 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 23,153 | Y |
| CRT_SORENTO_018 | PTBSFPHV51014 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 21,961 | Y |
| CRT_SUBARU_10 | PTBSFPLV01008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 22,923 | Y |
| CRT_SUBARU_11 | PTBSFPLV01008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 24,595 | Y |
| CRT_SUBARU_12 | PTBSFPLV01008 | 74 / 23.3 | 76 / 24.4 | 70 / 21.1 | 52 | 60 | 48 | 20,498 | Y |

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.