



ISO/IEC 19752 Yield Test Report
MX310 High Yield Print Cartridge
 Printer MX310

Declaration of Yield:

Average Cartridge Yield	10,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 12,586
Std Dev 859
90% Lower Confidence 12,324

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	3-May-2012	10-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS120586A0E	4514PTB300383		71	72	69	53	58	48	14,140	Y
(S)CAS120586A1D	4514PTB300383		71	72	69	53	58	48	12,462	Y
(S)CAS120586907	4514PTB300383		71	72	69	53	58	48	13,224	Y
(S)CAS120586A31	4514PTB300401		71	72	69	53	58	48	12,470	Y
(S)CAS1205869D4	4514PTB300401		71	72	69	53	58	48	12,150	Y
(S)CAS120586953	4514PTB300401		71	72	69	53	58	48	11,886	Y
(S)CAS120586A33	4514PTB300403		71	72	69	53	58	48	13,515	Y
(S)CAS120586A32	4514PTB300403		71	72	69	53	58	48	13,912	Y
(S)CAS1205869F7	4514PTB300403		71	72	69	53	58	48	11,947	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.