



## ISO/IEC 19752 Yield Test Report

### MX310 Print Cartridge

Printer MX310

Declaration of Yield:	<b>Average Cartridge Yield      2,500      Standard Pages</b> <b>Declared yield in accordance with ISO/IEC 19752</b>
-----------------------	---

**Average 4,129**  
**Std Dev 452**  
**90% Lower Confidence 3,849**

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b>start</b>	<b>stop</b>
<b>Date Tested</b>	1-May-2012	2-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS610 Series(G3)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1205970F7	4514PTB300383	71	73	70	53	56	49	4,118	Y	
(S)CAS120586F55	4514PTB300383	71	73	70	53	56	49	4,002	Y	
(S)CAS120586F6C	4514PTB300383	71	73	70	53	56	49	3,925	Y	
(S)CAS1205970F0	4514PTB300401	71	73	70	53	56	49	3,938	Y	
(S)CAS1205970F2	4514PTB300401	71	73	70	53	56	49	3,679	Y	
(S)CAS120586F6B	4514PTB300401	71	73	70	53	56	49	3,917	Y	
(S)CAS120586F54	4514PTB300403	71	73	70	53	56	49	4,157	Y	
(S)CAS120586F5A	4514PTB300403	71	73	70	53	56	49	4,164	Y	
(S)CAS120586F4D	4514PTB300403	71	73	70	53	56	49	5,264	Y	

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.