



ISO/IEC 19752 Yield Test Report

MX317 Print Cartridge

Printer: MX317

Declaration of Yield:	Average Cartridge Yield	2,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 4,129
Std Dev 452
90% Lower Confidence 3,849

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 1-May-2012	<u>stop</u> 2-May-2012
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Orange Paper - 80gsm - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MX610 Series (B35)	
Operating system	Windows XP SP3	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	(S)CAS1205970F7	4514PTB300383	71	73	70	53	56	49	4,118	Y
	(S)CAS120586F55	4514PTB300383	71	73	70	53	56	49	4,002	Y
	(S)CAS120586F6C	4514PTB300383	71	73	70	53	56	49	3,925	Y
	(S)CAS1205970F0	4514PTB300401	71	73	70	53	56	49	3,938	Y
	(S)CAS1205970F2	4514PTB300401	71	73	70	53	56	49	3,679	Y
	(S)CAS120586F6B	4514PTB300401	71	73	70	53	56	49	3,917	Y
	(S)CAS120586F54	4514PTB300403	71	73	70	53	56	49	4,157	Y
	(S)CAS120586F5A	4514PTB300403	71	73	70	53	56	49	4,164	Y
	(S)CAS120586F4D	4514PTB300403	71	73	70	53	56	49	5,264	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.