



ISO/IEC 19752 Yield Test Report

MX321 Print Cartridge Printer MX321

Declaration of Yield:	Average Cartridge Yield	6,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 6,549
Std Dev 181
90% Lower Confidence 6,437

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 12-Sep-2017	<u>stop</u> 19-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS1723624F8	GSMPTB4600027	72	75	68	46	49	42	6,728	Y
SCAS172362522	GSMPTB4600027	72	75	68	46	49	42	6,577	Y
SCAS17236251F	GSMPTB4600027	72	75	68	46	49	42	6,782	Y
SCAS1723624F9	GSMPTB4600007	72	75	68	46	49	42	6,332	Y
SCAS172362532	GSMPTB4600007	72	75	68	46	49	42	6,377	Y
SCAS17236251C	GSMPTB4600007	72	75	68	46	49	42	6,461	Y
SCAS1723624E4	GSMPTB7017220	72	75	68	46	49	42	6,737	Y
SCAS172362527	GSMPTB7017220	72	75	68	46	49	42	6,626	Y
SCAS172362519	GSMPTB7017220	72	75	68	46	49	42	6,325	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.