

MX321 Toner Cartridge

Printer: MX321adn

Declaration of Yield:

Average Cartridge Yield	15,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 15,327
Std Dev 240
90% Lower Confidence 15,179

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	17-Aug-2017	7-Sep-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake 2nd shake	
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17170253E	GSMPTB4600027	73	77	70	56	60	49	15,612	Y
CAS171702558	GSMPTB4600027	73	77	70	56	60	49	15,674	Y
CAS171702533	GSMPTB4600027	73	77	70	56	60	49	15,023	Y
CAS17170253D	GSMPTB4600007	73	77	70	56	60	49	15,305	Y
CAS171702546	GSMPTB4600007	73	77	70	56	60	49	15,013	Y
CAS171702545	GSMPTB4600007	73	77	70	56	60	49	15,114	Y
CAS171702536	GSMPTB7017220	73	77	70	56	60	49	15,461	Y
CAS171702557	GSMPTB7017220	73	77	70	56	60	49	15,368	Y
CAS171702552	GSMPTB7017220	73	77	70	56	60	49	15,376	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.