ISO/IEC 19752 Yield Test Report

MX331 Starter Toner Cartridge

Printer: MX331adn

Declaration of Yield: **Average Cartridge Yield 1,500 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average	2,580
Std Dev	108
90% Lower Confidence	2,513

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	stop
Date tested	17-Oct-2019	17-Oct-2019

Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark Printer Software G4 v1.2
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
SCAD192697F65	460192400005D	72	73	71	57	58	56	2,595	Y
SCAD192697F69	460192400005D	72	73	71	57	58	56	2,520	Y
SCAD192697F59	460192400005D	72	73	71	57	58	56	2,380	Y
SCAD192697F56	460192400005C	72	73	71	57	58	56	2,590	Y
SCAD192697F67	460192400005C	72	73	71	57	58	56	2,790	Y
SCAD192697F66	460192400005C	72	73	71	57	58	56	2,545	Y
SCAD192697F57	7019924000009	72	73	71	57	58	56	2,610	Y
SCAD192697F68	7019924000009	72	73	71	57	58	56	2,630	Y
SCAD192697F58	7019924000009	72	73	71	57	58	56	2,560	Y

Comments and or exceptions:

1.) The print file was generated with number of copies set equal to 5.
2.) EOL was determined by a print starvation or fade.

Revision date 12/9/2019