

## MX331 High Yield Toner Cartridge

Printer: MX331adn

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>15,000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 15,512  
**Std Dev** 346  
**90% Lower Confidence** 15,297

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start 22-Oct-2019      stop 29-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
Cartridge	Printer								
SCAD192707F8D	460192400005D	73	75	71	53	58	48	15,235	Y
SCAD192707F82	460192400005D	73	75	71	53	58	48	15,090	Y
SCAD192707F87	460192400005D	73	75	71	53	58	48	15,385	Y
SCAD192707F83	460192400005C	73	75	71	53	58	48	16,045	Y
SCAD192707F8C	460192400005C	73	75	71	53	58	48	15,780	Y
SCAD192707F8F	460192400005C	73	75	71	53	58	48	15,785	Y
SCAD192707F86	7019924000009	73	75	71	53	58	48	15,740	Y
SCAD192707F89	7019924000009	73	75	71	53	58	48	15,060	Y
SCAD192707F92	7019924000009	73	75	71	53	58	48	15,485	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the print starvation or fade.