

MX331 Toner Cartridge

Printer: MX331adn

Declaration of Yield:

Average Cartridge Yield	3,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 3,906
Std Dev 168
90% Lower Confidence 3,801

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 18-Oct-2019 stop 19-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192707FC2	460192400005D	72	74	71	53	58	49	3,965	Y
	SCAD192707FD0	460192400005D	72	74	71	53	58	49	3,635	Y
	SCAD192707FC5	460192400005D	72	74	71	53	58	49	4,120	Y
	SCAD192707FCF	460192400005C	72	74	71	53	58	49	4,105	Y
	SCAD192707FC9	460192400005C	72	74	71	53	58	49	4,035	Y
	SCAD192707FC8	460192400005C	72	74	71	53	58	49	3,875	Y
	SCAD192707FBF	7.01992E+12	72	74	71	53	58	49	3,810	Y
	SCAD192707FC4	7.01992E+12	72	74	71	53	58	49	3,715	Y
	SCAD192707FC1	7.01992E+12	72	74	71	53	58	49	3,890	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.