

LEXMARK ISO/IEC 19752 Yield Test Report

MX410 Ship With Equipment Print Cartridge Printer MX410

Declaration of Yield: **Average Cartridge Yield 5,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 6,772
Std Dev 546
90% Lower Confidence 6,434

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	7-May-2012	10-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg (F/C)	(F/C)	(F/C)	Avg	Max	Min		
	(S)CAS120586F9C	4514PTB301038	73	78	72	43	48	39	6,253	Y
	(S)CAS120586F8D	4514PTB301038	73	78	72	43	48	39	7,864	Y
	(S)CAS120586F46	4514PTB301038	73	78	72	43	48	39	6,958	Y
	(S)CAS120586F8A	4514PTB301088	73	78	72	43	48	39	7,235	Y
	(S)CAS120586F67	4514PTB301088	73	78	72	43	48	39	6,782	Y
	(S)CAS120586F63	4514PTB301088	73	78	72	43	48	39	6,910	Y
	(S)CAS120586F83	4514PTB300751	73	78	72	43	48	39	6,266	Y
	(S)CAS120586F7B	4514PTB300751	73	78	72	43	48	39	6,469	Y
	(S)CAS120586F41	4514PTB300751	73	78	72	43	48	39	6,214	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.