



ISO/IEC 19752 Yield Test Report

MX417 Print Cartridge

Printer: MX417

Declaration of Yield:	Average Cartridge Yield	2,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,654
Std Dev 150
90% Lower Confidence 3,561

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 7-May-2012	<u>stop</u> 9-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
(S)CAS120586F50	4514PTB300302	73	78	69	51	55	39	3,546	Y
(S)CAS120586FDE	4514PTB300302	73	78	69	51	55	39	3,789	Y
(S)CAS120586F90	4514PTB300302	73	78	69	51	55	39	3,663	Y
(S)CAS120586FCE	4514PTB300307	73	78	69	51	55	39	3,433	Y
(S)CAS120586FCF	4514PTB300307	73	78	69	51	55	39	3,525	Y
(S)CAS120586FDF	4514PTB300307	73	78	69	51	55	39	3,759	Y
(S)CAS120586F4F	4514PTB300145	73	78	69	51	55	39	3,924	Y
(S)CAS120586F5C	4514PTB300145	73	78	69	51	55	39	3,635	Y
(S)CAS1205970DE	4514PTB300145	73	78	69	51	55	39	3,616	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.