



ISO/IEC 19752 Yield Test Report

MX417 High Yield Print Cartridge Printer MX417

Declaration of Yield:	Average Cartridge Yield	8,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 9,413
Std Dev 268
90% Lower Confidence 9,246

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 22-Feb-2017	<u>stop</u> 25-Feb-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS410 XL Series
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAB17031434D	70156PLM14X6X	72	73	71	55	58	53	9,742	Y
SCAB170314338	70156PLM14X6X	72	73	71	55	58	53	9,648	Y
SCAB1703142FA	70156PLM14X6X	72	73	71	55	58	53	9,110	Y
SCAB170314348	45146PLM3527G	72	73	71	55	58	53	9,649	Y
SCAB1703142F9	45146PLM3527G	72	73	71	55	58	53	8,976	Y
SCAB170314335	45146PLM3527G	72	73	71	55	58	53	9,228	Y
SCAB1703142E5	45146PLM3527K	72	73	71	55	58	53	9,418	Y
SCAB17031435D	45146PLM3527K	72	73	71	55	58	53	9,596	Y
SCAB1703142F2	45146PLM3527K	72	73	71	55	58	53	9,346	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.