



ISO/IEC 19752 Yield Test Report

MX421 High Yield Print Cartridge Printer MX421

Declaration of Yield:	Average Cartridge Yield	15,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 15,514
Std Dev 255
90% Lower Confidence 15,356

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 14-Aug-2017	<u>stop</u> 29-Aug-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS171702531	GSMPTB4600061	73	77	70	56	60	49	15,203	Y
SCAS171702559	GSMPTB4600061	73	77	70	56	60	49	15,520	Y
SCAS171702555	GSMPTB4600061	73	77	70	56	60	49	15,740	Y
SCAS17170254F	GSMPTB4600043	73	77	70	56	60	49	15,582	Y
SCAS171702541	GSMPTB4600043	73	77	70	56	60	49	15,093	Y
CAS17170254E	GSMPTB4600043	73	77	70	56	60	49	15,469	Y
SCAS171702534	GSMPTB7017257	73	77	70	56	60	49	15,886	Y
SCAS171702556	GSMPTB7017257	73	77	70	56	60	49	15,713	Y
SCAS171702553	GSMPTB7017257	73	77	70	56	60	49	15,416	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.