



ISO/IEC 19752 Yield Test Report

MX421 Extra High Yield Print Cartridge Printer MX421

Declaration of Yield:	Average Cartridge Yield	20,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 20,854
Std Dev 622
90% Lower Confidence 20,468

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 6-Sep-2017	<u>stop</u> 19-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS171702564	GSMPTB4600061	73	77	70	56	60	49	21,166	Y
SCAS171702570	GSMPTB4600061	73	77	70	56	60	49	20,429	Y
SCAS171702584	GSMPTB4600061	73	77	70	56	60	49	21,424	Y
SCAS171702589	GSMPTB4600043	73	77	70	56	60	49	20,189	Y
SCAS171702579	GSMPTB4600043	73	77	70	56	60	49	20,373	Y
SCAS17170257C	GSMPTB4600043	73	77	70	56	60	49	20,038	Y
SCAS171702560	GSMPTB7017257	73	77	70	56	60	49	21,671	Y
SCAS17170256C	GSMPTB7017257	73	77	70	56	60	49	21,550	Y
SCAS171702592	GSMPTB7017257	73	77	70	56	60	49	20,842	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.