



ISO/IEC 19752 Yield Test Report

MX421 Print Cartridge Printer MX421

Declaration of Yield:	Average Cartridge Yield	6,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 6,482
Std Dev 209
90% Lower Confidence 6,352

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 19-Sep-2017	<u>stop</u> 21-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS172362517	GSMPTB4600061	73	77	70	56	60	49	6,694	Y
SCAS17236251E	GSMPTB4600061	73	77	70	56	60	49	6,726	Y
SCAS17236251D	GSMPTB4600061	73	77	70	56	60	49	6,431	Y
SCAS172362526	GSMPTB4600043	73	77	70	56	60	49	6,570	Y
SCAS172362518	GSMPTB4600043	73	77	70	56	60	49	6,252	Y
SCAS17236251B	GSMPTB4600043	73	77	70	56	60	49	6,215	Y
SCAS17236250B	GSMPTB7017257	73	77	70	56	60	49	6,705	Y
SCAS17236252A	GSMPTB7017257	73	77	70	56	60	49	6,239	Y
SCAS17236252E	GSMPTB7017257	73	77	70	56	60	49	6,503	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.