

MX431 High Yield Toner Cartridge

Printer: MX431adn/adw

Declaration of Yield:

Average Cartridge Yield	15,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 15,909
Std Dev 363
90% Lower Confidence 15,684

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 21-Oct-2019 stop 25-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
Cartridge	Printer								
SCAD192707F94	701992400002G	73	75	71	53	58	48	15,530	Y
SCAD192707F84	701992400002G	73	75	71	53	58	48	16,600	Y
SCAD192707F90	701992400002G	73	75	71	53	58	48	16,150	Y
SCAD192707F85	701992400001N	73	75	71	53	58	48	15,635	Y
SCAD192707F8B	701992400001N	73	75	71	53	58	48	15,660	Y
SCAD192707F8E	701992400001N	73	75	71	53	58	48	16,085	Y
SCAD192707F8A	460192400003L	73	75	71	53	58	48	16,020	Y
SCAD192707F81	460192400003L	73	75	71	53	58	48	16,020	Y
SCAD192707F93	460192400003L	73	75	71	53	58	48	15,480	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the print starvation or fade.