



ISO/IEC 19752 Yield Test Report

MX51X High Yield Print Cartridge

Printer MX510 / MX511

Declaration of Yield: **Average Cartridge Yield 10,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 11,660
Std Dev 498
90% Lower Confidence 11,351

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	11-May-2012	17-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
	(S)CAS120586968	4514PTB301088	74	78	69	41	49	36	11,420	Y
	(S)CAS12058692E	4514PTB301088	74	78	69	41	49	36	11,442	Y
	(S)CAS1205869D5	4514PTB301088	74	78	69	41	49	36	10,869	Y
	(S)CAS1205869AC	4514PTB300747	74	78	69	41	49	36	11,757	Y
	(S)CAS1205869BE	4514PTB300747	74	78	69	41	49	36	11,634	Y
	(S)CAS1205869AF	4514PTB300747	74	78	69	41	49	36	11,314	Y
	(S)CAS1205869EE	4514PTB300749	74	78	69	41	49	36	12,626	Y
	(S)CAS120586A20	4514PTB300749	74	78	69	41	49	36	12,076	Y
	(S)CAS1205869BF	4514PTB300749	74	78	69	41	49	36	11,803	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.