



ISO/IEC 19752 Yield Test Report

MX51X Print Cartridge

Printer MX510 / MX511

Declaration of Yield:	Average Cartridge Yield 2,500 Standard Pages Declared yield in accordance with ISO/IEC 19752
-----------------------	---

Average 3,766
Std Dev 174
90% Lower Confidence 3,658

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	1-May-2012	5-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAS1205970D1	4514PTB301088	4514PTB301088	71	73	69	53	58	49	3,862	Y
(S)CAS120586F5B	4514PTB301088	4514PTB301088	71	73	69	53	58	49	3,704	Y
(S)CAS1205970E5	4514PTB301088	4514PTB301088	71	73	69	53	58	49	3,774	Y
(S)CAS1205970F1	4514PTB301038	4514PTB301038	71	73	69	53	58	49	3,967	Y
(S)CAS1205970E1	4514PTB301038	4514PTB301038	71	73	69	53	58	49	3,955	Y
(S)CAS1205970D2	4514PTB301038	4514PTB301038	71	73	69	53	58	49	3,924	Y
(S)CAS120597107	4514PTB300751	4514PTB300751	71	73	69	53	58	49	3,501	Y
(S)CAS120586FDB	4514PTB300751	4514PTB300751	71	73	69	53	58	49	3,558	Y
(S)CAS120586F92	4514PTB300751	4514PTB300751	71	73	69	53	58	49	3,650	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.