



ISO/IEC 19752 Yield Test Report

MX521/MX522 Ultra High Yield Print Cartridge Printer MX521/MX522

Declaration of Yield:	Average Cartridge Yield	25,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 26,423
Std Dev 431
90% Lower Confidence 26,156

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 25-Sep-2017	<u>stop</u> 10-Oct-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS1717025AF	GSMPTB4600074	73	77	70	56	60	49	26,790	Y
SCAS1717025A1	GSMPTB4600074	73	77	70	56	60	49	25,639	Y
SCAS1717025B9	GSMPTB4600074	73	77	70	56	60	49	26,561	Y
SCAS17170259C	GSMPTB4600096	73	77	70	56	60	49	26,087	Y
SCAS1717025BC	GSMPTB4600096	73	77	70	56	60	49	26,763	Y
SCAS1717025B6	GSMPTB4600096	73	77	70	56	60	49	26,114	Y
SCAS1717025B5	GSMPTB7017325	73	77	70	56	60	49	26,550	Y
SCAS1717025BB	GSMPTB7017325	73	77	70	56	60	49	27,021	Y
SCAS1717634D8F	GSMPTB7017325	73	77	70	56	60	49	26,281	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.