



ISO/IEC 19752 Yield Test Report

MX521/MX522 High Yield Print Cartridge Printer MX521/MX522

Declaration of Yield:	Average Cartridge Yield	15,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 15,647
Std Dev 323
90% Lower Confidence 15,447

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 29-Aug-2017	<u>stop</u> 12-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS171702549	GSMPTB4600074	73	77	70	56	60	49	15,631	Y
SCAS171702554	GSMPTB4600074	73	77	70	56	60	49	15,411	Y
SCAS17170251D	GSMPTB4600074	73	77	70	56	60	49	15,043	Y
CAS171702537	GSMPTB4600096	73	77	70	56	60	49	15,728	Y
CAS171702551	GSMPTB4600096	73	77	70	56	60	49	15,528	Y
CAS17170254C	GSMPTB4600096	73	77	70	56	60	49	15,605	Y
SCAS171702535	GSMPTB7017325	73	77	70	56	60	49	16,068	Y
SCAS171702547	GSMPTB7017325	73	77	70	56	60	49	16,108	Y
SCAS17170254A	GSMPTB7017325	73	77	70	56	60	49	15,704	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.