

MX532 Toner Cartridge

Printer: MX532adwe

Declaration of Yield:

Average Cartridge Yield	28,400	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 29,163
Std Dev 587
90% Lower Confidence 28,799

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 17-Nov-2022 **stop** 1-Dec-2022

Number of cartridges in testing	9	9
Qty. of cartridges used in calculation	9	9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark Printer Software G3 XL
Operating system		Windows 10 Enterprise
Application software		Adobe Acrobat Reader DC ver. 2021.007.20099
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAA22315000E	4602FST SCT107	72	72	72	45	45	45	29,636	Y
	SCAA22315000A	4602FST SCT107	72	72	72	45	45	45	28,899	Y
	SCAA223150011	4602FST SCT107	72	72	72	45	45	45	28,851	Y
	SCAA223150014	7020FST NLE014	72	72	72	45	45	45	29,412	Y
	SCAA223150010	7020FST NLE014	72	72	72	45	45	45	28,992	Y
	SCAA22315000D	7020FST NLE014	72	72	72	45	45	45	28,982	Y
	SCAA223150005	7020FST NLE033	72	72	72	45	45	45	29,375	Y
	SCAA223150004	7020FST NLE033	72	72	72	45	45	45	30,209	Y
	SCAA223150006	7020FST NLE033	72	72	72	45	45	45	28,113	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.