



## ISO/IEC 19752 Yield Test Report

### MX61X High Yield Print Cartridge

Printer MX610 / MX611

Declaration of Yield: **Average Cartridge Yield 10,000 Standard Pages**  
**Declared yield in accordance with ISO/IEC 19752**

**Average** 11,867  
**Std Dev** 587  
**90% Lower Confidence** 11,504

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b>start</b>	<b>stop</b>
<b>Date Tested</b>	14-May-2012	17-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
	(S)CAS120586A18	4514PTB300198	72	75	68	45	50	40	11,420	Y
	(S)CAS120586A1A	4514PTB300198	72	75	68	45	50	40	11,222	Y
	(S)CAS120586A1C	4514PTB300198	72	75	68	45	50	40	12,377	Y
	(S)CAS1205869AB	4514PTB300207	72	75	68	45	50	40	11,363	Y
	(S)CAS1205869B7	4514PTB300207	72	75	68	45	50	40	11,193	Y
	(S)CAS120586A1B	4514PTB300207	72	75	68	45	50	40	11,796	Y
	(S)CAS1205869D3	4514PTB300608	72	75	68	45	50	40	12,618	Y
	(S)CAS1205869D1	4514PTB300608	72	75	68	45	50	40	12,330	Y
	(S)CAS1205869AA	4514PTB300608	72	75	68	45	50	40	12,487	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.