



ISO/IEC 19752 Yield Test Report

MX61X Extra High Yield Print Cartridge

Printer MX610 / MX611

Declaration of Yield: **Average Cartridge Yield 20,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 21,881
Std Dev 1,150
90% Lower Confidence 21,168

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	18-May-2012	24-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
	(S)CAS120586A18	4514PTB300198	75	78	68	42	50	38	22,960	Y
	(S)CAS120586A1A	4514PTB300198	75	78	68	42	50	38	22,381	Y
	(S)CAS120586A1C	4514PTB300198	75	78	68	42	50	38	20,172	Y
	(S)CAS1205869AB	4514PTB300207	75	78	68	42	50	38	23,210	Y
	(S)CAS1205869B7	4514PTB300207	75	78	68	42	50	38	21,383	Y
	(S)CAS120586A1B	4514PTB300207	75	78	68	42	50	38	20,922	Y
	(S)CAS1205869D3	4514PTB300608	75	78	68	42	50	38	21,900	Y
	(S)CAS1205869D1	4514PTB300608	75	78	68	42	50	38	20,718	Y
	(S)CAS1205869AA	4514PTB300608	75	78	68	42	50	38	23,279	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.