



ISO/IEC 19752 Yield Test Report

MX622 High Yield Print Cartridge Printer MX622

Declaration of Yield:	Average Cartridge Yield	15,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 15,425
Std Dev 451
90% Lower Confidence 15,146

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 12-Sep-2017	<u>stop</u> 20-Sep-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS1717024C2	GSMPTB7018369	73	77	70	56	60	49	15,104	Y
SCAS17170252E	GSMPTB7018369	73	77	70	56	60	49	15,166	Y
SCAS171702514	GSMPTB7018369	73	77	70	56	60	49	15,251	Y
SCAS17170253A	GSMPTB4600160	73	77	70	56	60	49	15,410	Y
SCAS17170251A	GSMPTB4600160	73	77	70	56	60	49	14,663	Y
SCAS17170253C	GSMPTB4600160	73	77	70	56	60	49	15,678	Y
SCAS17170254B	GSMPTB4600134	73	77	70	56	60	49	15,607	Y
SCAS171702529	GSMPTB4600134	73	77	70	56	60	49	16,244	Y
SCAS171702515	GSMPTB4600134	73	77	70	56	60	49	15,703	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.