



# ISO/IEC 19752 Yield Test Report

## MX622 Extra High Yield Print Cartridge Printer MX622

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>20,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 20,799  
**Std Dev** 617  
**90% Lower Confidence** 20,417

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

[=

<b>Date Tested</b>	<u>start</u> 21-Sep-2017	<u>stop</u> 2-Oct-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS171702583	GSMPTB7018369	73	77	70	56	60	49	19,884	Y
CAS171702585	GSMPTB7018369	73	77	70	56	60	49	20,196	Y
SCAS171702582	GSMPTB7018369	73	77	70	56	60	49	20,385	Y
SCAS171702581	GSMPTB4600160	73	77	70	56	60	49	20,420	Y
SCAS171702576	GSMPTB4600160	73	77	70	56	60	49	21,329	Y
SCAS17170256E	GSMPTB4600160	73	77	70	56	60	49	20,674	Y
SCAS171702566	GSMPTB4600134	73	77	70	56	60	49	21,531	Y
SCAS171702574	GSMPTB4600134	73	77	70	56	60	49	21,379	Y
SCAS17170258A	GSMPTB4600134	73	77	70	56	60	49	21,397	Y

### Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.