



ISO/IEC 19752 Yield Test Report

MX717 Print Cartridge
Printer: MX717

Declaration of Yield: **Average Cartridge Yield 11,000 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 13,249
Std Dev 514
90% Lower Confidence 12,930

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 20-Apr-2017	<u>stop</u> 24-Apr-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX710 Series XL
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAB170901598	40636C6600YFX	73	74	72	58	60	57	12,757	Y
SCAB170901587	40636C6600YFX	73	74	72	58	60	57	12,976	Y
SCAB170901573	40636C6600YFX	73	74	72	58	60	57	13,886	Y
SCAB1709014E0	40636C6600YFW	73	74	72	58	60	57	13,760	Y
SCAB1709014E3	40636C6600YFW	73	74	72	58	60	57	13,795	Y
SCAB170901520	40636C6600YFW	73	74	72	58	60	57	13,456	Y
SCAB17090153F	40636C6604PXZ	73	74	72	58	60	57	13,320	Y
SCAB170901536	40636C6604PXZ	73	74	72	58	60	57	12,817	Y
SCAB17090156C	40636C6604PXZ	73	74	72	58	60	57	12,475	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.