



# ISO/IEC 19752 Yield Test Report

## MX718 Print Cartridge

Printer: MX718

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>11,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 13,377  
**Std Dev** 967  
**90% Lower Confidence** 12,777

**For questions concerning testing contact**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 20-Apr-2017	<u>stop</u> 24-Apr-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX710 Series XL
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAB1709014EF	74635C6600GBY	73	74	72	58	60	57	14,191	Y
SCAB170901500	74635C6600GBY	73	74	72	58	60	57	14,520	Y
SCAB1709014E2	74635C6600GBY	73	74	72	58	60	57	14,862	Y
SCAB170901553	74635C6603G1L	73	74	72	58	60	57	12,308	Y
SCAB1709014F6	74635C6603G1L	73	74	72	58	60	57	13,309	Y
SCAB17090158D	74635C6603G1L	73	74	72	58	60	57	13,406	Y
SCAB17090157B	74635C6600GBZ	73	74	72	58	60	57	12,129	Y
SCAB17090151C	74635C6600GBZ	73	74	72	58	60	57	12,847	Y
SCAB17090156F	74635C6600GBZ	73	74	72	58	60	57	12,817	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.