



ISO/IEC 19752 Yield Test Report

MX721/MX824 High Yield Print Cartridge

Printer: MX721/MX824

Declaration of Yield:	Average Cartridge Yield	15,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 17,462
Std Dev 569
90% Lower Confidence 17,110

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 22-Jan-2018	<u>stop</u> 25-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS1732100D5	4064PTBGLA165	73	76	72	51	53	49	17,298	Y
	CAS1732100A4	4064PTBGLA165	73	76	72	50	53	48	17,462	Y
	CAS1732100C2	4064PTBGLA165	73	76	72	50	53	48	16,439	Y
	CAS1732100CF	4064PTBGLA166	73	76	72	51	53	49	17,475	Y
	CAS1732100A2	4064PTBGLA166	73	76	72	50	53	48	17,210	Y
	CAS1732100BA	4064PTBGLA166	73	76	72	50	53	48	17,201	Y
	CAS1732100EF	4064PTBGLA173	73	76	72	51	53	49	17,649	Y
	CAS1732100EE	4064PTBGLA173	73	76	72	50	53	48	18,544	Y
	CAS1732100BC	4064PTBGLA173	73	76	72	50	53	48	17,883	Y

Comments and or exceptions:

*The print file was generated with number of copies set equal to 5.

*EOL was determined by the printer calling for the cartridge to be replaced.