



ISO/IEC 19752 Yield Test Report

MX721/MX824 Extra High Yield Print Cartridge Printer MX721/MX824

Declaration of Yield:	Average Cartridge Yield	35,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 37,959
Std Dev 3,111
90% Lower Confidence 36,031

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 6-Feb-2018	<u>stop</u> 10-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17321019F	4064PTBGLA165	73	75	72	51	53	50	39,513	Y
CAS1732101A6	4064PTBGLA165	73	75	72	50	53	49	33,468	Y
CAS173210132	4064PTBGLA165	73	75	72	50	53	49	39,366	Y
CAS1732101A7	4064PTBGLA166	73	75	72	51	53	50	38,812	Y
CAS17321019D	4064PTBGLA166	73	75	72	51	53	49	33,865	Y
CAS17321014F	4064PTBGLA166	73	75	72	50	53	49	39,411	Y
CAS173210134	4064PTBGLA173	73	75	72	51	53	50	41,558	Y
CAS17321019A	4064PTBGLA173	73	75	72	51	53	49	34,636	Y
CAS17321014B	4064PTBGLA173	73	75	72	50	53	49	41,001	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.