



# ISO/IEC 19752 Yield Test Report

## MX721/MX824 Ultra High Yield Print Cartridge Printer MX721/MX824

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>55,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 60,309  
**Std Dev** 3,209  
**90% Lower Confidence** 58,320

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 25-Jan-2018	<u>stop</u> 3-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1732101FE	4064PTBGLA165	73	75	72	50	54	47	61,512	Y
CAS17321022D	4064PTBGLA165	73	76	73	50	52	48	60,787	Y
CAS1732101F4	4064PTBGLA165	73	76	73	50	54	48	58,251	Y
CAS173210218	4064PTBGLA166	73	75	72	50	54	47	60,352	Y
CAS17321020D	4064PTBGLA166	73	76	73	50	52	48	62,551	Y
CAS1732101D2	4064PTBGLA166	73	76	73	50	54	48	56,827	Y
CAS1732101F9	4064PTBGLA173	73	75	72	50	54	47	63,541	Y
CAS173210226	4064PTBGLA173	73	76	73	50	52	48	64,352	Y
CAS1732101D5	4064PTBGLA173	73	76	73	50	54	48	54,608	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.