



ISO/IEC 19752 Yield Test Report

MX721/MX824 Print Cartridge

Printer: MX721/MX824

Declaration of Yield:	Average Cartridge Yield	7,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 7,857
Std Dev 607
90% Lower Confidence 7,542

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 3-Feb-2017	<u>stop</u> 6-Feb-2018
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17320125B	4064PTBGLA165	73	74	72	51	54	49	7,497	Y
CAS1732012D3	4064PTBGLA165	73	74	73	51	53	49	7,454	Y
CAS173201252	4064PTBGLA165	73	75	72	51	53	49	7,792	Y
CAS1732012C5	4064PTBGLA165	73	75	72	51	52	50	7,094	Y
CAS173201284	4064PTBGLA166	73	74	72	51	54	49	8,033	Y
CAS173201234	4064PTBGLA166	73	74	73	51	53	49	7,814	Y
CAS173201292	4064PTBGLA166	73	75	72	51	53	49	8,227	Y
CAS173201257	4064PTBGLA166	73	75	72	51	52	50	8,854	Y
CAS173201296	4064PTBGLA173	73	74	72	51	54	49	6,970	Y
CAS173201247	4064PTBGLA173	73	74	73	51	53	49	7,547	Y
CAS17320126C	4064PTBGLA173	73	75	72	51	53	49	8,109	Y
CAS173201237	4064PTBGLA173	73	74	73	51	53	49	8,888	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.