



# ISO/IEC 19752 Yield Test Report

## MX722/MX826 Starter Print Cartridge

Printer: MX722/MX826

Declaration of Yield	<b>Average Cartridge Yield</b>	<b>11,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 12,134  
**Std Dev** 351  
**90% Lower Confidence** 11,917

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 11-Jan-2018	<u>stop</u> 12-Jan-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173201111	4064PTBGLA162	74	76	73	49	50	48	12,004	Y
CAS173201110	4064PTBGLA162	74	76	73	50	53	48	12,467	Y
CAS1732010E5	4064PTBGLA162	74	76	73	50	53	48	12,358	Y
CAS173201101	4064PTBGLA163	74	76	73	49	50	48	12,426	Y
CAS17320110D	4064PTBGLA163	74	76	73	50	53	48	12,097	Y
CAS17320118C	4064PTBGLA163	74	76	73	50	53	48	12,359	Y
CAS173201125	4064PTBGLA164	74	76	73	49	50	48	11,370	Y
CAS173201123	4064PTBGLA164	74	76	73	50	53	48	11,865	Y
CAS1732010E2	4064PTBGLA164	74	76	73	50	53	48	12,263	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.