



ISO/IEC 19752 Yield Test Report

MX722/MX826 High Yield Print Cartridge

Printer: MX722/MX826

Declaration of Yield:	Average Cartridge Yield	15,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 16,778
Std Dev 330
90% Lower Confidence 16,573

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 22-Jan-2018	<u>stop</u> 25-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS1732100F9	4064PTBGLA162	73	76	72	51	53	49	16,398	Y
	CAS1732100B2	4064PTBGLA162	73	76	72	50	53	48	16,559	Y
	CAS1732100BB	4064PTBGLA162	73	76	72	50	53	48	16,837	Y
	CAS1732100D7	4064PTBGLA163	73	76	72	51	53	49	16,999	Y
	CAS1732100A3	4064PTBGLA163	73	76	72	50	53	48	17,476	Y
	CAS1732100ABF	4064PTBGLA163	73	76	72	50	53	48	16,947	Y
	CAS1732100F3	4064PTBGLA164	73	76	72	51	53	49	16,668	Y
	CAS1732100A9	4064PTBGLA164	73	76	72	50	53	48	16,594	Y
	CAS1732100AC	4064PTBGLA164	73	76	72	50	53	48	16,522	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.