



# ISO/IEC 19752 Yield Test Report

## Mx722/MX826 Ultra High Yield Print Cartridge Printer Mx722/MX826

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>55,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 61,260  
**Std Dev** 1,595  
**90% Lower Confidence** 60,271

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 25-Jan-2018	<u>stop</u> 3-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210209	4064PTBGLA162	73	75	72	50	54	47	61,450	Y
CAS1732101C5	4064PTBGLA162	73	75	73	50	52	48	62,355	Y
CAS1732101F1	4064PTBGLA162	74	76	73	50	54	48	62,116	Y
CAS173210200	4064PTBGLA163	73	75	72	50	54	47	58,924	Y
CAS173210221	4064PTBGLA163	73	75	73	50	52	48	62,710	Y
CAS1732101D3	4064PTBGLA163	74	76	73	50	54	48	63,251	Y
CAS1732100E2	4064PTBGLA164	73	75	72	50	54	47	58,766	Y
CAS1732101DE	4064PTBGLA164	73	75	73	50	52	48	60,458	Y
CAS1732101D0	4064PTBGLA164	74	76	73	50	54	48	61,312	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.