



# ISO/IEC 19752 Yield Test Report

## MX722/MX826 Print Cartridge

Printer: MX722/MX826

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>7,500</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 8,932  
**Std Dev** 317  
**90% Lower Confidence** 8,735

**For questions concerning testing contact**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 3-Feb-2018	<u>stop</u> 6-Feb-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS173201258	4064PTBGLA162	73	74	72	51	54	49	9,195	Y
	CAS173201283	4064PTBGLA162	73	74	72	51	54	49	9,006	Y
	CAS17320126F	4064PTBGLA162	73	74	72	51	54	49	8,690	Y
	CAS17320122C	4064PTBGLA163	73	74	72	51	54	49	9,262	Y
	CAS173201233	4064PTBGLA163	73	74	72	51	54	49	9,098	Y
	CAS173201270	4064PTBGLA163	73	74	72	51	54	49	9,347	Y
	CAS173201235	4064PTBGLA164	73	74	72	51	54	49	8,484	Y
	CAS173201282	4064PTBGLA164	73	74	72	51	54	49	8,697	Y
	CAS173201231	4064PTBGLA164	73	74	72	51	54	49	8,605	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.