



ISO/IEC 19752 Yield Test Report

MX725 Starter Print Cartridge

Printer: MX725

Declaration of Yield	Average Cartridge Yield	11,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 12,768
Std Dev 550
90% Lower Confidence 12,427

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 11-Jan-2018	<u>stop</u> 13-Jan-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1732010E3	4064PTBGLA174	74	76	73	49	50	48	12,456	Y
CAS1732011CA	4064PTBGLA174	74	76	73	50	53	48	12,595	Y
CAS173201128	4064PTBGLA174	73	76	72	50	53	48	12,565	Y
CAS1732010FD	4064PTBGLA175	74	76	73	49	50	48	13,014	Y
CAS1732011A9	4064PTBGLA175	74	76	73	50	53	48	13,756	Y
CAS17320110B	4064PTBGLA175	73	76	72	50	53	48	13,456	Y
CAS173201195	4064PTBGLA176	74	76	73	49	50	48	12,042	Y
CAS17320113E	4064PTBGLA176	74	76	73	50	53	48	12,303	Y
CAS173201113	4064PTBGLA176	73	76	72	50	53	48	12,723	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.