



ISO/IEC 19752 Yield Test Report

MX722/MX826 Extra High Yield Print Cartridge Printer MX722/MX826

Declaration of Yield:	Average Cartridge Yield	35,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752			

Average 39,342
Std Dev 3,369
90% Lower Confidence 37,254

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 6-Feb-2018	<u>stop</u> 10-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS173210196	4064PTBGLA162	73	75	72	51	53	50	40,332	Y
CAS173210192	4064PTBGLA162	73	75	72	51	53	49	40,705	Y
CAS173210150	4064PTBGLA162	73	75	72	50	53	49	39,477	Y
CAS173210198	4064PTBGLA163	73	75	72	51	53	50	42,295	Y
CAS17321019B	4064PTBGLA163	73	75	72	51	53	49	42,496	Y
CAS173210152	4064PTBGLA163	73	75	72	50	53	49	40,953	Y
CAS173210197	4064PTBGLA164	73	75	72	51	53	50	38,692	Y
CAS173210153	4064PTBGLA164	73	75	72	51	53	49	37,775	Y
CAS17321013E	4064PTBGLA164	73	75	72	50	53	49	31,355	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.