



ISO/IEC 19752 Yield Test Report

MX725 Ultra High Yield Print Cartridge Printer MX725

Declaration of Yield:	Average Cartridge Yield	55,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 64,191
Std Dev 2,559
90% Lower Confidence 62,604

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	16-Jan-2018	29-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1732101C8	4064PTBGLA175	72	75	65	52	64	48	65,405	Y
CAS173210224	4064PTBGLA175	73	76	72	51	53	48	69,342	Y
CAS1732101FF	4064PTBGLA175	73	75	73	50	54	48	66,051	Y
CAS1732101D9	4064PTBGLA176	72	75	65	52	64	48	61,357	Y
CAS173210230	4064PTBGLA176	73	76	72	51	53	48	64,172	Y
CAS1732101FB	4064PTBGLA176	73	75	73	50	54	48	62,893	Y
CAS1732101D6	4064PTBGLA174	72	75	65	52	64	48	61,052	Y
CAS17321022E	4064PTBGLA174	73	76	72	51	53	48	64,400	Y
CAS173210228	4064PTBGLA174	73	75	73	50	54	48	63,043	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.