



ISO/IEC 19752 Yield Test Report

MX725 Print Cartridge Printer MX725

Declaration of Yield:	Average Cartridge Yield	7,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 8,927
Std Dev 570
90% Lower Confidence 8,574

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 29-Jan-2018	<u>stop</u> 30-Jan-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17320120A	4064PTBGLA175	74	75	73	50	52	49	9,281	Y
CAS1732012AC	4064PTBGLA175	74	75	73	50	52	49	9,587	Y
CAS173201298	4064PTBGLA175	74	75	73	50	52	49	9,145	Y
CAS17320121A	4064PTBGLA176	74	75	73	50	52	49	8,996	Y
CAS173201277	4064PTBGLA176	74	75	73	50	52	49	9,065	Y
CAS173201276	4064PTBGLA176	74	75	73	50	52	49	9,414	Y
CAS173201217	4064PTBGLA174	74	75	73	50	52	49	8,579	Y
CAS17320121F	4064PTBGLA174	74	75	73	50	52	49	8,568	Y
CAS17320127B	4064PTBGLA174	74	75	73	50	52	49	7,710	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.