

LEXMARK TM ISO/IEC 19752 Yield Test Report

MX811 Extra High Yield Print Cartridge Printer MX811

Declaration of Yield:

Average Cartridge Yield	45,000	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 48,543
Std Dev 1,455
90% Lower Confidence 47,641

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 31-May-2012	<u>stop</u> 11-Jun-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - A4
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Gold 9
Operating system		Windows XP SP3
Application software		Acrobat version 9.1
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
(S)CAN1210704D5	4063127900002	72	75	68	42	48	38	50,545	Y
(S)CAN1210704B9	4063127900002	72	75	68	42	48	38	50,680	Y
(S)CAN1210704B8	4063127900002	72	75	68	42	48	38	49,495	Y
(S)CAN1210704D4	406312790000Y	72	75	68	42	48	38	47,765	Y
(S)CAN1210704D6	406312790000Y	72	75	68	42	48	38	47,775	Y
(S)CAN1210704BD	406312790000Y	72	75	68	42	48	38	46,460	Y
(S)CAN121080370	40631279000085	72	75	68	42	48	38	48,525	Y
(S)CAN1210704D7	40631279000085	72	75	68	42	48	38	47,160	Y
(S)CAN1210704BB	40631279000085	72	75	68	42	48	38	48,480	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.