



ISO/IEC 19752 Yield Test Report

MX822 Extra High Yield Print Cartridge Printer MX822

Declaration of Yield:	Average Cartridge Yield	35,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 39,720
Std Dev 1,131
90% Lower Confidence 39,019

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 3-Feb-2018	<u>stop</u> 9-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No shake No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) evreyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS17210191	4064PTBGLA159	73	75	72	51	53	49	38,874	Y
CAS17210193	4064PTBGLA159	73	75	72	51	53	50	39,041	Y
CAS173210195	4064PTBGLA159	73	75	72	51	53	49	40,913	Y
CAS1721014C	4064PTBGLA160	73	75	72	51	53	49	40,128	Y
CAS1721019E	4064PTBGLA160	73	75	72	51	53	50	39,456	Y
CAS17210194	4064PTBGLA160	73	75	72	51	53	49	37,906	Y
CAS17321014D	4064PTBGLA161	73	75	72	51	53	49	41,325	Y
CAS1732101A0	4064PTBGLA161	73	75	72	51	53	50	40,305	Y
CAS1732101A5	4064PTBGLA161	73	75	72	51	53	49	40,033	Y

s

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 10.
- 2.) EOL was determined by the printer calling for the cartridge to be replaced.