



ISO/IEC 19752 Yield Test Report

MX822 Ultra High Yield Print Cartridge Printer MX822

Declaration of Yield:	Average Cartridge Yield	55,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 62,663
Std Dev 1,807
90% Lower Confidence 61,543

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date Tested	16-Jan-2018	29-Jan-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1732101DA	4064PTBGLA159	72	75	65	52	64	48	59,876	Y
CAS1732101B7	4064PTBGLA159	73	76	72	51	53	48	64,431	Y
CAS1732101FD	4064PTBGLA159	73	75	73	50	54	48	64,266	Y
CAS1732101B3	4064PTBGLA160	72	75	65	52	64	48	59,384	Y
CAS1732101B4	4064PTBGLA160	73	76	72	51	53	48	63,059	Y
CAS173210202	4064PTBGLA160	73	75	73	50	54	48	63,549	Y
CAS1732101CD	4064PTBGLA161	72	75	65	52	64	48	63,233	Y
CAS17321020F	4064PTBGLA161	73	76	72	51	53	48	63,466	Y
CAS17321020A	4064PTBGLA161	73	75	73	50	54	48	62,706	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.