



ISO/IEC 19752 Yield Test Report

MX822 Print Cartridge

Printer: MX822

Declaration of Yield:	Average Cartridge Yield	7,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 8,701
Std Dev 222
90% Lower Confidence 8,563

For questions concerning testing contact
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 29-Jan-2018	<u>stop</u> 30-Jan-2018
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	47_G3	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS173201212	4064PTBGLA159	74	75	73	50	52	49	8,972	Y
	CAS173201214	4064PTBGLA159	74	75	73	50	52	49	8,676	Y
	CAS17320120E	4064PTBGLA159	74	75	73	50	52	49	8,665	Y
	CAS173201297	4064PTBGLA160	74	75	73	50	52	49	8,554	Y
	CAS173201213	4064PTBGLA160	74	75	73	50	52	49	8,241	Y
	CAS17320120F	4064PTBGLA160	74	75	73	50	52	49	8,770	Y
	CAS173201216	4064PTBGLA161	74	75	73	50	52	49	8,777	Y
	CAS17320121B	4064PTBGLA161	74	75	73	50	52	49	8,676	Y
	CAS17320120D	4064PTBGLA161	74	75	73	50	52	49	8,975	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.